

WERRA-PERFECT MANHOLE BASES MANHOLE BODY, CHANNEL AND BERM IN ONE POUR

DN 600-1500 MM

NOMINAL DIAMETER	EXTERIAL HEIGHT	CLEAR HEIGHT approx.	WALL THICKNESS	CONNECTION max.	WEIGHT approx.	LAYING ANCHOR weight class
DN	H	h	t	DN	kg/Pc.	t
mm	mm	mm	mm	mm		
600	500	400	65	150	200	-
600	500	400	65	200	200	-
600	500	400	65	250	200	-
1000	700	550	150	150	1400	3 x 1,5 - 2,5
1000	750	600	150	200	1460	3 x 1,5 - 2,5
1000	800	650	150	250	1500	3 x 1,5 - 2,5
1000	850	700	150	300	1600	3 x 1,5 - 2,5
1000	950	800	190	400	2000	3 x 1,5 - 2,5
1000	1050	900	190	500	2150	3 x 1,5 - 2,5
1000	1150	1000	230	600	2500	3 x 1,5 - 2,5
1200	700	550	190	150	1900	3 x 3 - 5
1200	750	600	190	200	2000	3 x 3 - 5
1200	800	650	190	250	2100	3 x 3 - 5
1200	850	700	190	300	2200	3 x 3 - 5
1200	950	800	190	400	2500	3 x 3 - 5
1200	1050	900	190	500	2900	3 x 3 - 5
1200	1350	1200	300	600	4450	3 x 3 - 5
1200	1350	1200	300	700	4350	3 x 3 - 5
1200	1350	1200	300	800	4250	3 x 3 - 5
1500	750	550	380	150	5150	3 x 3 - 5
1500	800	600	380	200	5500	3 x 3 - 5
1500	850	650	380	250	5800	3 x 3 - 5
1500	900	700	380	300	6100	3 x 3 - 5
1500	1000	800	380	400	6700	3 x 3 - 5
1500	1100	900	380	500	7300	3 x 3 - 5
1500	1200	1000	380	600	7000	3 x 3 - 5
1500	1300	1100	380	700	6500	3 x 3 - 5
1500	1400	1200	380	800	6100	3 x 3 - 5
1500	1500	1300	380	900	5700	3 x 3 - 5
1500	1600	1400	380	1000	5500	3 x 3 - 5